

DECLARATION OF PERFORMANCE EC CONSTRUCTION PRODUCTS REGULATION EN 12326 ROOFING AND CLADDING SLATE

DOP Number			192024		
Unique Identification Code of the Product Type			Stoneleaf SL11		
2. Product Origin			China		
3. Intended use or uses of the construction product, in accordance as foreseen by the manufacturer.	Slate & carbonate slate for discontinuous Roofing and Cladding				
4. Name, registered name, or trademark and contact address of th	Stoneleaf Building Materials, Templewood Industrial Estate, Stock Road, West Hanningfield, Chelmsford, CM2 8LA				
5. Where applicable, name and contact address of the authorised representative.			N/A		
6. System or systems of assessment and verification of constancy of performance			AVCP System 4		
7. Declared Performance					
Essential Characteristics for Pitched Roof Coverings	Performance				Harmonised Technical Specification
Mechanical Resistance	Average MOR:				
	Transverse	39.46 Mpa	Longitudinal	49.58 Mpa	
	Characteristic MOR:				7
	Transverse	33.4 Mpa	Longitudinal	31.6 Mpa	7
External Fire Performance	Deemed to satisfy				
Reaction to Fire	Deemed to satisfy Class A1				
Dimensional Tolerances	•				
	Very Flat	Smooth	Normal	Textured	
Deviation from Flatness	0.4%				BS EN 12326-2: 2014
Nominal Thickness & Variation	6mm +/- 8.3%				
Deviation from Declared Length	0.0%				
Deviation from Declared Width	0.0%				
Deviation from squareness	0.6%				
Durability					
Water Absorption	W1 (0.35%)				
Freeze Thaw	Not required				
Thermal Cycle Test	T1 (No changes in appearance)				
SO2 Exposure Test ≤ 20%	S1 (No change after exposure)				
Non-Carbonate Carbon Content	0.7%				
Release of Dangerous Substances	None in conditions of use as roofing or external cladding				

The product(s) identified in Points 1 and 2 are in conformity with the declared performance in Point 7. This declaration of performance is the sole responsibility of the manufacturer identified in Point 4.

Authorised by:



